



i6310 Accessories Brochure



Standard Cradle



Volume Sensor



Wrist Strap & Protective Boot



Multifunctional Cradle



Scan Trigger Handle with Charger

Volume Sensor A630

- Using the principle of structured light to quickly obtain three-dimensional volume parameters of goods
- Precise—Measurement Deviation within 1%
- Fast—Obtain volume data in 0.2s
- Convenient—Easy to assemble and disassemble
- Portable—only 100g
- Support i6310 Series only



Scan Trigger Handle with Charger : TRPW630

- Ergonomic design, specially designed for high-intensity scanning work.
- Built-in 4500mAh battery, mobile charging, meeting long working hours.
- Removable, easy to install and disassemble.
- Support i6310 Series only.



LED Indicator Status

Discharge State		Charge State	
LED Status	Electricity Status	LED Status	Electricity Status
red light flashing	0%–5%	red light flashing	0%–25%
red light long	5%–25%	yellow light flashing	26%–75%
yellow light long	26%–75%	green light flashing	≥ 76%
green light long	≥ 76%	green light long	≥ 76%

Multifunctional Cradle

- Charge one handle separately
 - Charge one handle and one device simultaneously
 - Support multiple cradle aggregated
-
- Input 5V 2.6A
 - Interface DC Jack
 - Charging contacts life cycle: 5000 times
-





Single slot charger



Support multiple cradle aggregated

Standard Cradle

Charging one device	
Input	5V 1.5A
Interface	DC Jack
Charging contacts life cycle	more than 5000 times

Fingerprint reader



- Adopt top-level fingerprint verification module and algorithm, quickly and accurately identify fingerprints, fully guarantee user login security.
- Reinforced glass coating, more wear resistant.

Others



Wrist Strap and Protective Boot

- Specially designed for mobile applications
- Improve protection performance
- Adjustable elastic wristband



Power Adapter

- Applicable for charging handle or multifunctional cradle
- Input: 100–240V~50/60Hz 0.6A



Type-C Data Cable

- Applicable for charging and data transmission
- Interface: Type-C



Power Adapter

- Applicable for charging device or standard cradle with Type-C cable
- Input: 100–240V~50/60Hz 0.4A
- Output: 5V 1.5A