

# D8000 Series Thermal Transfer Label Printer

4"

Print on the first sheet of paper

Automatic proofreading paper, The first paper starts printing, Not waste

Automatic paper measurement function

Transmission and reflection type sensor Automatic measuring paper, Print more accurately

Super fast printing speed

Regular width label, Print at most per second 10+ (Sheet)

Diversified transmission interface

USB+Serial port + parallel port  
Optional : Ethernet/wifi/Bluetooth

Super paper capacity

Regular size label, Load paper once, Printable 1000+ (Sheet) label

Support multi-function printing

Support heat transfer printing/Thermosensitive switch at will, Supports multiple label printing



# D8000 Series Thermal Transfer Label Printer



## Performance parameter

|                           |   |                      |   |
|---------------------------|---|----------------------|---|
| Dimension (W x D x H)     | 278mm*210mm*180mm   | Ribbon width         | 30mm-110mm  |
| Weight                    | 2.6Kg   | Paper Roll OD        | 130mm (OD)  |
| Printing Method           | Heat transfer/Direct thermal  | Ribbon diameter      | 67mm  |
| Memory                    | RAM:8M FLASH:4M/8M  | Maximum print width  | 104mm   |
| Print Mode                | Ribbon/Direct thermal   | Maximum print length | 2286mm (90" )   |
| Paper Type                | Continuous paper, paper with interspaces, folding paper, black mark paper         | Ribbon length        | 300m  |
| Paper Width               | 20mm-120mm  | Work Environment     | 5 ~ 45 °C   |
| Print Speed               | 152mm/s   | Storage Environment  | -10 ~ 50 °C   |
| Dot density               | 203DPI/300DPI   | Work Humidity        | 25 ~85 % non-condensing                                   |
| Thermal film(reliability) | 50 km   | Storage Humidity     | 10 ~90 % non-condensing                                   |
| Interface                 | 3 interface (Serial port+USB+parallel port)<br>Optional: Ethernet, wif, Bluetooth | Optional Accessories | Paper holder frame/Label cutter/Wash the water mug cutter |
| Power Supply              | Input: AC 110V/240V<br>Output: DC 24V/2.5A, 60W                                   |                      |   |

## Accessories



## Urovo Technology Co., Ltd.

- Tel: 400 888 6989 ● Website: [www.urovo.com](http://www.urovo.com) ● E-mial: [urovo@urovo.com](mailto:urovo@urovo.com)
- Address: Floor 36, Hitech Zone Union Tower, No.63 Xuefu Road, Nanshan District, Shenzhen, China.

The content of this page will be updated from time to time due to product line adjustment. Subject to change without prior notice.